





.mdd

FABRICS


NEMO




NE-16




NE-14



NE-10




NE-17




NE-15


Group I



NE-1




NE-9



NE-2



NE-3



NE-5


RUNNER




R-60999



R-60025



R-60011



R-66063



R-66064

Group II



R-61128



R-68056



R-61130



R-63034




R-64089

MEDLEY



M-60999




M-66008



M-67053



M-67006




M63064

Group II




M-61002



M-68002



M-68115




M-68005




M-64019


ATLANTIC



A-60025



A-60011



A-60141



A-65037



A-66064

Group II




A-61078



A-62048



A-67030




A-67043



A-64089


VITA



V-07



V-04



V-01



V-15



V-19

Group II



V-02



V-06



V-03




V-05



V-08




V-18



V-20



V-23




V-12

RIVER


Group II



RV-100




RV-91




RV-79




RV-24



RV-28




RV-41




RV-51




RV-21



RV-34




RV-38



RV-87

XTREME CS


Group III



XR009



XR081



XR094



XR026



XR084



XR108



XR430



XR160



XR420



XR079


XTREME YS

Group III



YS071

SYNERGY



LDS27



LDS29



LDS20



LDS08



LDS61




LDS53



LDS50




LDS60




LDS69



LDS57



LDS84




LDS85



LDS86



LDS88



LDS79




LDS19



LDS44

NOTE




N - 60051




N - 61148




N - 68156



N - 68155



N - 61125




N - 63036

Group III

Group III


FIELD 2



FD-192




FD-142




FD-132




FD-123



FD-782



FD-963




FD-463



FD-662



FD-673




FD-693

Group IV

ATLAS



AS-391



AS-111



AS-161



AS-781



AS-681



AS-981



AS-971



AS-531



AS-501



AS-651

Group IV

ALCANTARA



Brown 4180



Anthracite 6422

Group V

LEATHER

Group IV



L01



L02



L03



L04



L05



L06



L07

Price group	Fabric	Material	Weight	Abrasion resistance rubs	Pilling resistance	Colour fastness to light	Colour fastness to rubbing	Flammability	More information
I	NEMO	Polyester 100%	366g/m2	PN-EN ISO 12947 - 2:2 100,000	Scale 1-8, max 8, PN-EN ISO 105 B02:2013 3-4	Scale 1-5, max 5, PN-EN 1021 - 2:2007, PN-EN 1021 - 1:2007	Scale 1-5, max 5, EN ISO 105x12, (wet/dry) 4-5		
II	RUNNER	Polyester 100%	320g/m2, 510g/lm	70,000 Martindale, BS EN 14465, EN ISO 12947-2	Scale 1-5, max 5, EN ISO 12945-2 4-5	Scale 1-8, max 8, EN ISO 105-B02 5-7	Scale 1-5, max 5, EN ISO 105x12, (wet/dry) 4-5	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, California Bulletin CAL 117-E-Class 1, CA TB 117-2013, Class Uno UNI 9175 Class 1	Acoustic test sound absorption ISO 354
II	MEDLEY	Polyester 100%	364g/m2, 510g/lm	75,000 Martindale	Scale 1-5, max 5, EN ISO 12945-2 4	Scale 1-8, max 8, EN ISO 105-B02 5-7	Scale 1-5, max 5, EN ISO 105x12, (wet/dry) 4-5/4-5	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, California Bulletin CAL 117-E-Class 1, CA TB 117-2013, Class Uno UNI 9175 Class 1	Acoustic test sound absorption: ISO 354
II	ATLANTIC	Polyester 100%	353g/m2, 530g/lm	110,000 Martindale, EN ISO 12947-2)		Scale 1-8, max 8, EN ISO 105-B02 5-7	Scale 1-5, max 5, EN ISO 105x12, (wet/dry) 4-5/4-5	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, ASTM E 84, BS 476 Part 7, Class Uno UNI 9175 Class 1, NF P 92-503 M3P, CA TB 117-2013	
II	VITA	Surface: PVC, 98.5%, PU 1.5% Substrate: Polyester 50%, 50% Cotton	850g/m2, 1190g/lm	100,000 Martindale, EN ISO 5470-2:2003,		Scale 1-8, max 8, EN ISO 105-B02 5-7	Scale 1-5, max 5, EN ISO 105x12, (wet/dry) 4-5/4-5	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5852:2006 Section 4, Ignition Source 5, BS 7176:2017 Medium Hazard NF P 95 503 M2, FMVSS 302 (ISO 3795)	Flexing cycles: BS EN ISO 7854:1997 Method B, 400.000, Anti-microbial/ Anti-fungal: AATCC 147:2011
II	RIVER	Polyester 100%	300g/m2	100,000 Martindale, EN ISO 12947-1,2	EN ISO 12945-2 5	ISO 105-B02 4	ISO 105-X12:2001, (wet/dry) 3/4-5	BS 5852: Part 1: 1979, Ignition source 0 Cigarette, BS 5852: Part 1: 1979, Ignition source 1 Match, EN1021-2	
III	XTREME CS / YS	Trevira Clame 100% (CS), Recycled 100% (YS), Non metallic dyestuffs, Flame Retardant polyester	310g/m2 435g/lm	60,000 Martindale		ISO 105 B02: 6	ISO 105-X12:2001, (wet/dry) 4/4	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 7176 Low Hazard NF P92-507 M1, DIN 4102 B1, UNI 9175 Classe 1 IM, UNI 8456, UNI 9174 & UNI 9177 Classe Uno, ÖNORM B 3825 & A 3800-1, NF D 60-013 (only CS)	
III	SYNERGY	Virgin Wool 95%, Polyamide 5%	400g/m2 560g/lm	100,000 Martindale		ISO 105 B02: 5	ISO 105-X12:2001, (wet/dry) 4/4	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 7176 Low Hazard. UNI 9175 Classe 1 IM, ÖNORM B 3825 & A 3800-1	
III	NOTE	Wools of New Zealand 85%, Polyamide 15%	510g/m2	200,000 Martindale EN ISO 12947-2		ISO 105 B02: 8	ISO 105-X12:2001, (wet/dry) 4/4-5	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5852 source 1&0, CA TB 117-2013, MED. Certificate IMO	
IV	FIELD 2	100% Trevira CS	321g/m2 450g/lm	100,000 Martindale EN ISO 12947	EN ISO 12945-2 4-5	ISO 105 B02: 5-7		BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5852 Crib 5, DIN 4102 B1 FAR 25.853, CA TB 117-2013, MED. Certificate IMO, NF P 92 507 M1, UNI 9177 classe 1, US Cal. Bull. 117-2013	
IV	ATLAS	New wool 90% Nylon 10%	286g/m2 400g/lm	100,000 Martindale EN ISO 12947	EN ISO 12945-2 4-5	ISO 105 B02: 6-7	ISO 105-X12:2001, (wet/dry) 4-5/4-5	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5 5852 Crib 5, BS 5852 Ignition source 3, BS 5852 Part 1, NF D 60 013, UNI 9175 1IM, US Cal. Bull. 117-2013, MED. CertificateIMO	
IV	LEATHER	Leather type - corrected grain leather Type of finishing - pigmented leather		Dry: 500 cycles - min. 4 grey scale Wet: 250 cycles - min. 4 grey scale UNI EN ISO 11640		Light fastness: min. 4 grey scale UNI ISO 105-802		Match flame test: No ignition UNI EN 1021-1-2006 BS EN 1021-1-2006	
V	ALCANTARA	Polyester 68% Poliuretano 32%	450g/m2	150,000 Martindale EN ISO 12947-2	EN ISO 12945-2 2000 cycles, ≥4/5,	AATCC-16A > 4	ISO 105-X12:2001, (wet/dry) 3/4	BS EN 1021-2 Match, BS EN 1021-1 Cigarette, BS 5852 Crib 5 (sect. 3)	